AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

- (Withdrawn) A paste containing:
 solids having a conductive substance and a resin; and
 a solvent for dissolving the resin,
 wherein a solids content of said paste is not less than 60 vol%.
- (Withdrawn) A paste containing:
 solids having a conductive substance and a resin; and
 a solvent for dissolving the resin,
 wherein a viscosity ratio of said paste is not more than 2.
- 3. (Withdrawn) A paste containing: solids having a conductive substance and a resin; and a solvent for dissolving the resin, wherein a solids content of said paste is not less than 60 vol% and a viscosity ratio thereof is not more than 2.
 - 4. (Cancelled)

5. (Withdrawn) A method of burying a paste in a trench formed in a major surface of a substrate, comprising:

forming said trench in said substrate; and

burying, in said trench, a paste containing solids having a conductive substance and a resin, and a solvent for dissolving the resin, wherein a solids content of said paste is not less than 60 vol%.

6. (Withdrawn) A method of burying a paste in a trench formed in a major surface of a substrate, comprising:

forming said trench in said substrate; and

burying, in said trench, a paste containing solids having a conductive substance and a resin; and a solvent for dissolving the resin, wherein a viscosity ration of said paste is not more than 2.

- 7. (Withdrawn) A method according to claim 5, wherein a viscosity ratio of said paste is not more than 2.
 - 8. (Cancelled)
- 9. (Currently Amended) A method of burying powder in a trench <u>having a</u>

 <u>bottom</u> formed in a major surface of a substrate <u>by coating, comprising:</u>

applying a dispersion of the powder in a solvent onto a region including the trench with a solution in which the powder disperses; and

precipitating the powder in the solution dispersion within the trench to bury the trench with the precipitated powder.

- 10. (Currently amended) A method according to claim 9, wherein a solution to which a resin is added is used as the solution the dispersion contains a resin.
- 11. (Original) A method according to claim 9, wherein a portion of said powder is a glass powder.
- 12. (Original) A method according to claim 10, wherein a portion of said powder is a glass powder.

13-24. (Cancelled)

- 25. (Withdrawn) A method according to claim 5, further comprising polishing a lower surface of the substrate to expose the paste buried in said trench.
 - 26. (Withdrawn) A method according to claim 5,

wherein said forming the trench includes forming a plug hole in an upper surface of said substrate, and said burying includes burying said paste into said plug hole; and wherein said method further comprises:

removing the lower surface of the substrate until the paste buried at a bottom portion of said plug hole appears to form a chip-through plug.

- 27. (Withdrawn) A method according to claim 6, further comprising polishing a lower surface of the substrate to expose the paste buried in said trench.
 - 28. (Withdrawn) A method according to claim 6,

wherein said forming the trench includes forming a plug hole in an upper surface of said substrate, and said burying includes burying said paste into said plug hole, and wherein said method further comprises:

removing the lower surface of the substrate until the paste buried at a bottom portion of said plug hole appears to form a chip-through plug.

- 29. (Currently Amended) A method according to claim 9, further comprising polishing a lower surface of the substrate to expose the powder buried in said trench.
 - 30. (Currently Amended) A method according to claim 9,

wherein said forming the trench includes a plug hole <u>having a bottom formed</u> in an upper surface of said substrate, and said <u>burying precipitating</u> includes <u>burying</u> <u>precipitating</u> said <u>paste into powder within</u> said plug hole; and wherein said method further comprises:

removing the lower surface of the substrate until the powder buried at a bottom portion of said plug hole appears to form a chip-through plug.